



(mm)		Ae	Be	He	Ai	Bi	Hi		Pozice	
201N/10	Neporovaný	1350	750	850	1300	700	670	Ø 125	A (B-C)	L 610
201N/20	Neporovaný	1180	685	850	1130	635	670	Ø 125	A (B-C)	L 480
201N/30	Neporovaný	1050	650	850	1000	600	670	Ø 125	A (B-C)	L 400
201N/40	Neporovaný	1070	550	775	1020	500	620	Ø 100	A (B-C)	L 316
201N/50	Neporovaný	860	510	650	810	460	500	Ø 100	C (B)	L 186
201F/10	Perforovaný	1350	750	850	1300	700	670	Ø 125	A (B-C)	L 610
201F/20	Perforovaný	1180	685	850	1130	635	670	Ø 125	A (B-C)	L 480
201F/30	Perforovaný	1050	650	850	1000	600	670	Ø 125	A (B-C)	L 400
201F/40	Perforovaný	1070	550	775	1020	500	620	Ø 100	A (B-C)	L 316
201F/50	Perforovaný	860	510	650	810	460	500	Ø 100	C (B)	L 186

Pozice



Konstruován s horizontálně vystuženými zdi o tlošťce cca 120mm. Zdi a dno jsou kompletně uzavřeny nebo perforovány.